



Certificate number: 2403734 (2)

Issued 28/03/2024

Expires 26/03/2029

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

BONOMI INDUSTRIES s.r.l.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

CERTIFICATE

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:
BONOMI INDUSTRIES s.r.l.
Via Padana Superiore
29 - 25080 Mazzano (BS)
Italy



KUKreg4

Product Certificate

Appendix to Certificate number: 2403734

The following products belong to this certificate

| |
|--|
| <p>PRODUCT DESCRIPTION Range of spherical valves with brass bodies and PTFE seats. ATS3 – Without Production Surveillance.</p> |
| <p>MODEL(S) S20XYZ s.20 in size range ¼" - 2" BSP (FxF / MxF) S24XYZ s.24 in size range ½" - 2" BSP (FxF / MxF) S28XYZ s.28 12mm and 15mm COMPRESSION INLET/OUTLET suitable for copper tubes according to EN 1057. X = valve size B: ¼" C: ⅜" or 12mm D: ½" or 15mm E: ¾" F: 1" G: 1¼" H: 1½" I: 2" YY = type of thread and handle 00: (BSPP (F)x(F), lever handle), 06: (BSPP (F)x(F), T-handle), T0: (BSPP (F)x(F), Stubby lever) 15: (BSPP (F)x(F), Lockable handle) 20: (BSPP (M)x(F), lever handle), 26: (BSPP (M)x(F), T-handle), 25: (BSPP (M)x(F), Lockable handle) T20: (BSPP (M)x(F), Stubby lever). Z = handle colour A: light blue, B: blue, K: black, M: return spring lever, R: red, W: green.</p> |
| <p>SIZE: See model.</p> |
| <p>SCOPE: Manufacturer recommended maximum working pressure: s.20 – 30 bar, s.24 - 30 bar, s.28 – 16 bar & maximum operating temperature 85°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 85°C.</p> |
| <p>MARKING RUB logo on body.</p> |
| <p>MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.</p> |
| <p>BACKFLOW PROTECTION NOTES N/A.</p> |
| <p>ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements.</p> |

Extra Notes